



## LCFLED-HVG-BLK

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT  
Hive, All Pictograms, Single or Double Sided, Black



### PRODUCT INFORMATION

Part Number	LCFLED-HVG-BLK
MIC	UKA00000001301
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4Ghz
Battery	Lithium Nanophosphate 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.046A
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Max)	12.5A / 82uS
Earth Leakage	0.33mA
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X   0   AD   180
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Strip
8003803	Driver Pack
8003250	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.