



## LCFLED-HVG

### CLEVERTRONICS L10 CLEVERFIT EXIT



PRODUCT INFORMATION	
Part Number	LCFLED-HVG
MIC	UKA01810010001
Description	L10 Optimum Cleverfit Emergency Exit
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



## LCFLED-HVG

CLEVERTRONICS L10 CLEVERFIT EXIT

PRODUCT INFORMATION				
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"><li>Battery overvoltage &amp; overcurrent protection</li><li>Battery deep discharge protection</li><li>Supply voltage polarity reversal protection</li><li>Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530090	BATTERY: L10 3.3V 2.5AH 390mm lead,noBrkt
8002710	LED: PCA:DurisLED Strip Clvrft Pro CT10276-D3
8002337	DRIVER: PCA:LCFLED Driver CT10164-L6 6C70 CTP UK OWC
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice