



## LCFLED-HVG

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive,  
All Pictograms, Single or Double Sided



PRODUCT INFORMATION	
Part Number	LCFLED-HVG
MIC	UKA01810010002
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4Ghz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Max)	12.5A / 82uS
Earth Leakage	0.33mA

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

PRODUCT INFORMATION					
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Strip
8003803	DRIVER
8003250	Hive Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice