



LCFLED-HV

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive,
All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LCFLED-HV
MIC	AUA01810010002
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby) 4.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3 C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II, noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATT:L10 3.3V 2.5AH 390mm lead, no BRKT
8002710	LED: PCA: Duris LED Strip Cleverfit Pro CT10276-D3
8002358	EM DRIVER: PCA: CT10164-L6 6C43-83 DALIREG, HV
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.