






LCFLED-TH-D2-R

Cleverfit Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man, Single Sided



PRODUCT INFORMATION

Part Number	LCFLED-TH-D2-R
MIC	AUA01260880001
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall or Ceiling, Single-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man, Single Sided
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar-100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.2 Watts (Standby), 3.6 Watts (Max)
Inrush Current (Peak/Duration)	17.1A/138µs
Earth Leakage	0.291mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC Purposes Only)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8003171	Drive Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.