



LCFLED-TH-DALI-RU



CLEVERTRONICS L10 CLEVERFIT LED EXIT - THEATRE



PRODUCT INFORMATION

Part Number	LCFLED-TH-DALI-RU
MIC	UKA01260010002
Description	L10 Optimum LED Cleverfit Emergency Exit with Theatre Mask
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.3W (Standby), 4.2W (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	X	1	ADF	180	
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking	 				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead, no Brkt
8002120	PCA:DLED Cleverfit Light Strip, CT10152-D5
8002329	PCA: CT10164-L6 6C43 DALI, Dali Reg, HV
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.