



LCFLED-TH-HVG-DS-RAOW

CLEVERTRONICS L10 CLEVERFIT EXIT, THEATRE, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

| | |
|--------------------------|---|
| Part Number | LCFLED-TH-HVG-DS-RAOW |
| MIC | AUA01960120002 |
| Description | L10 Optimum LED Cleverfit Emergency Exit with Theatre Mask |
| Construction | ABS Body and Diffuser with Clear Polycarbonate Tamper Proof Cover |
| Mounting | Wall or Ceiling Mounted, Double Sided |
| Dimensions L x W x H | 355mm x 80mm x 215mm |
| Weight | 1.8kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT Hive 2.4GHz |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre mask, Running Man Arrow One Way, Double Sided |
| Lamp(s) | 6 x LED, 100,000Hrs |
| Operating Voltage | 220V-240V AC: 50Hz |
| Power Consumption | 2.8 Watts (Standby), 4 Watts (Max) |
| Inrush Current (Max) | 12.537A, 82µS |
| Earth Leakage | 0.324mA |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530090 | Battery |
| 8002329 | Driver |
| 8002710 | LED Strip |
| 8003560 | HIVE Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.