



LCFLED-TH-HVG-RD

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks Hive, Theatre Version, Running Man Arrow Down, Single Sided



PRODUCT INFORMATION	
Part Number	LCFLED-TH-HVG-RD
MIC	UKA00000001001
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks Hive, Theatre Version, Running Man Arrow Down, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4Ghz
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictogram, Single Element (Running Man Arrow Down)
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.044A
Power Factor	0.368
Power Consumption	3.3W (Standby), 4.2W (Max)
Inrush Current (Peak/Duration)	12.5A/82µs
Earth Leakage	0.33mA
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X 1 AG 180
Conformity	BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance
Appliance Class	<input type="checkbox"/> Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Panel
8003801	Emergency Driver
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order