




LCFLED-TH-RD

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Down, Single Sided



PRODUCT INFORMATION

Part Number	LCFLED-TH-RD
MIC	UKA01360040001
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Down, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man with Down Arrow, Single Sided
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.0W (Standby), 3.9W (Max)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 1 AG 180
Conformity	 BS EN 60598-2-22 Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002356	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order