



LCFLED-TH-RR

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided



PRODUCT INFORMATION

| | |
|-----------------------------|---|
| Part Number | LCFLED-TH-RR |
| MIC | UKA01360030001 |
| Description | Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided |
| Construction | ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover |
| Dimensions L x W x H | 355mm x 80mm x 215mm |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery Type & Manufacturer | Lithium Nanophosphate, Clevertronics |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | 6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs |
| Operating Voltage | 220-240V AC; 50Hz |
| Power Consumption | 3.0W (Standby), 3.9W (Max) |

PRODUCT INFORMATION

| | | | | | |
|--------------------------|---|----|-----|----|-----|
| Rated Emergency Duration | 180 minutes | | | | |
| IP Rating | IP20 | | | | |
| Operating temperature | 0°C to 40°C | | | | |
| Protection | <ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts | | | | |
| Luminaire Classification | <table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table> | X | 1 | AG | 180 |
| X | 1 | AG | 180 | | |
| Applicable Standards | BS EN 60598-2-22, Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance | | | | |
| Compliance Marking | | | | | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530090 | Battery |
| 8002710 | LED Strip |
| 8002356 | Driver |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.