



LCFLED-TH-RR

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided



PRODUCT INFORMATION

Part Number	LCFLED-TH-RR
MIC	UKA01360030002
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictogram, Single Element (Running Man Arrow Right)
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.0W (Standby), 3.9W (Max)
Supply Current	0.044A
Power Factor	0.368
Inrush Current (Peak/Duration)	12.5A/82µs
Earth Leakage	0.33mA
Viewing Distance	30m
IP Rating	IP20
Rated Emergency Duration	180 minutes
Operating Temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X 1 AG 180
Conformity	BS EN 60598-2-22, Note: Dark format Theatre Exit products are not referenced in BS5499-4 and require a deviation and local sign off for compliance
Appliance Class	<input type="checkbox"/> Class II doubled insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Panel
8003805	Emergency Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.