



LCFLED-TH-RU

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Up, Single Sided



PRODUCT INFORMATION	
Part Number	LCFLED-TH-RU
MIC	UKA01360010001
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Up, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.0W (Standby), 3.9W (Max)

PRODUCT INFORMATION					
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">Battery overvoltage & overcurrent protectionBattery deep discharge protectionSupply voltage polarity reversal protectionBattery short-circuit protection (charging will resume upon removal of fault)Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AD</td><td>180</td></tr></table>	X	1	AD	180
X	1	AD	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002356	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.