



## LCFLED-UPS

CLEVERTRONICS L10 CLEVERFIT EXIT, UPS CONTROLLED



### PRODUCT INFORMATION

Part Number	LCFLED-UPS
MIC	AUA01510220001
Description	Cleverfit Emergency Exit. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.8kg
Operating Mode	Maintained with no integral battery backup (UPS)
Testing System	Clevertest Plus Enabled (Not activated by default)
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	3.1 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D4 C90=D3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8002306	Emergency Driver
8002710	Emergency LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.