

CLEVERTRONICS L10 CLEVERFIT EXIT



PRODUCT INFORMATION

Catalogue Number	LCFLED
MIC	UKA01310010002
Description	L10 Lithium Nanophosphate Cleverfit Emergency Exit with Clevertest Plus Enabled
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E5 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.45
Power Consumption	2.5 Watts (Standby), 4.5 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBrkt
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D3
8002338	PCA:LCFLED Driver CT10164-L6 6C70 CTP UK OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.