



## LCFLED

L10 Lithium Nanophosphate Cleverfit Emergency Exit with Clevertest Plus Enabled



### PRODUCT INFORMATION

Part Number	LCFLED			
MIC	UKA01310010003			
Description	L10 Lithium Nanophosphate Cleverfit Emergency Exit with Clevertest Plus Enabled			
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.8kg			
Operating Mode	Maintained			
Testing System	Clevertest Plus Enabled (Not activated by default)			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x Duris E5 LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Factor	0.45			
Power Consumption	2.5 Watts (Standby), 4.5 Watts (Max)			
Inrush Current (Max)	12.5A/82µs			
Earth Leakage	0.33mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598-2-22, BS 5266			

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Panel
8003804	Emergency Driver

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.