



LCFPRO-BLK

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms, Clevertest Plus Enabled, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	LCFPRO-BLK				
MIC	UKA00000002801				
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms, Clevertest Plus Enabled, Single or Double Sided, Black				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.5kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Factor	0.39				
Power Consumption	3.4 Watts (Standby), 4.1 Watts (Max)				
Inrush Current (Max)	12.8A/82µs				
Earth Leakage	0.339mA				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Compliance Marking					
Luminaire Classification	X	1	AG	180	
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Strip
8003858	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.