



LCFPRO-D2-BLK

L10 Optimum Cleverfit PRO Emergency Exit, DALI-2, Black



PRODUCT INFORMATION

Part Number	LCFPRO-D2-BLK
MIC	AUA00000034401
Description	L10 Optimum Cleverfit PRO Emergency Exit, DALI-2, Black
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E2 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.035A
Power Factor	0.36
Power Consumption	2.8W (Standby), 3.9W (Max)
Inrush Current (Peak/Duration)	12.851A / 82µs
Earth Leakage	0.347mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D3.2 C90=B16
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8003152	Emergency Driver
8002710	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.