



## LCFPRO-D2

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2  
Emergency, All Pictograms, Single or Double Sided



### PRODUCT INFORMATION

Part Number	LCFPRO-D2				
MIC	UKA00000002701				
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.5kg				
Operating Mode	Maintained				
Testing System	DALI-2				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)				
Inrush Current (Peak/Duration)	TBC				
Earth Leakage	TBC				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	1	AG	180	
Conformity	BS EN 60598-2-22, BS-5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Assembly
8003857	DALI-2 Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice