



LCFPRO-HVG-BLK

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms, Zoneworks XT Hive, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	LCFPRO-HVG-BLK			
MIC	UKA00000002601			
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms, Zoneworks XT Hive, Single or Double Sided, Black			
Construction	PC/ABS body with PC Diffuser			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	367mm x 72mm x 214mm			
Weight	2.5kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT Hive (RF), 2.4GHz			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x Duris E3 LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.7 Watts (Standby), 4.4 Watts (Max)			
Inrush Current (Max)	12.8A/82µs			
Earth Leakage	0.339mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)			
Luminaire Classification	X	1	AGF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Strip
8003857	Driver
8003330	Hive Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.