



LCFPRO-HVG

CLEVERTRONICS L10 CLEVERFIT PRO EXIT
(ZONWORKS HIVE)



PRODUCT INFORMATION				
Part Number	LCFPRO-HVG			
MIC	UKA01810050001			
Description	L10 Lithium Nanophosphate Cleverfit PRO Emergency Exit			
Construction	PC/ABS body with PC Diffuser			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	367mm x 72mm x 214mm			
Weight	2.5kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x Duris E3 LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 			
Luminaire Classification	X	1	AGF	180
Conformity	BS EN 60598.2.22, BS 5266			

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LCFPRO-HVG
CLEVERTRONICS L10 CLEVERFIT PRO EXIT
(ZONWORKS HIVE)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBrkt
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003151	PCA:CCF-Pro #CT10622 6C70 DReg HVG
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice