



## LCFPRO-HVG

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided



### PRODUCT INFORMATION

Part Number	LCFPRO-HVG				
MIC	UKA01810050002				
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.5kg				
Operating Mode	Maintained				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.7 Watts (Standby), 4.4 Watts (Max)				
Inrush Current (Max)	12.8A, 82us				
Earth Leakage	0.339mA				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AGF</td><td>180</td></tr></table>	X	1	AGF	180
X	1	AGF	180		
Conformity	BS EN 60598.2.22, BS 5266				

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Strip
8003857	Driver
8003330	Hive Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice