



LCFPRO-TH-HVG-DS-RAOW

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION	
Part Number	LCFPRO-TH-HVG-DS-RAOW
MIC	UKA0000000901
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man Arrow One Way, Double Sided
Material	PC/ABS body with PC Diffuser
Mounting	Ceiling - Single and Double Sided
Dimensions	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man with Arrow UP
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby) 3.9 Watts (Max)
Inrush Current (Max)	13A, 82uS
Earth Leakage	0.339mA
IP Rating	IP20
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Luminaire Classification	X 1 AFG 180
Conformity	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED Assembly
8003156	Emergency Driver
8003330	RF Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order