Cleverfit Pro Exit, Surface Mount, L10, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man Arrow Right, Single Sided



PRODUCT INFORMATION	
Catalogue Number	LCFPRO-TH-HVG-RR
MIC	AUA01960050001
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man Arrow Right, Single Sided
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, ceiling single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask Running Man with Arrow Right (Must specify diffuser combination)
Lamp(s)	6 x LED, 100,000
Operating Voltage	240V AC: 50Hz
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

