

## LCFPRO-TH-HVG-RU

Cleverfit Pro Exit, Surface Mount, L10, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man Arrow UP



PRODUCT INFORMATION	
Part Number	LCFPRO-TH-HVG-RU
MIC	UKA01860020001
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version Running Man Arrow UP
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man with Arrow UP
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> </ul>
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598.2.22, BS 5266

<sup>\*</sup>Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





## LCFPRO-TH-HVG-RU

Cleverfit Pro Exit, Surface Mount, L10, Zoneworks XT Hive 2.4GHz,
Theatre Version, Running Man Arrow UP

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED Strip
8003330	2.4Ghz RF Node
8003156	EM Driver

<sup>\*</sup>Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

