Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided



PRODUCT INFORMATION		
Catalogue Number	LCFPRO-TH-HVG-R	
MIC	AUA01960030001	
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided	
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser	
Mounting	Wall, ceiling single sided	
Dimensions L x W x H	367mm x 72mm x 214mm	
Weight	2.5kg	
Operating Mode	Maintained	
Testing System	Zoneworks XT HIVE (RF)	
Battery	Lithium Nanophosphate, 3.3V 2500mAh	
Charging Method	Intelligent current limited constant voltage	
Diffuser	Theatre Mask Running man (Must specify diffuser combination)	
Lamp(s)	6 x LED, 100,000	
Operating Voltage	240V AC: 50Hz	
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)	
IP Rating	IP20	
Operating Temperature	1°C to 40°C	
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A	
Viewing Distance	24m	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

