



LCFPRO-TH-RL

Cleverfit Pro Exit, Surface Mount, L10
Nanophosphate, Clevertest Plus, Theatre Version,
Running Man Arrow Left, Single Sided



PRODUCT INFORMATION

Part Number	LCFPRO-TH-RL
MIC	UKA00000003701
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Left, Single Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running Man with Arrow Left
Lamp(s)	6 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V~50Hz
Supply Current	0.035A
Power Factor	0.36
Power Consumption	2W (Standby), 3 (Max)
Inrush Current (Peak/Duration)	7.92A / 126µs
Earth Leakage	0.323mA
IP Rating	IP20
Operating temperature	0°C to 40°C
Viewing Distance	30m
Luminaire Classification	X 1 AG 180
Rated Emergency Duration	180 minutes
Compliance Marking	
Conformity	BS EN 60598-2-22, BS 5266



LCFPRO-TH-RL

Cleverfit Pro Exit, Surface Mount, L10
Nanophosphate, Clevertest Plus, Theatre Version,
Running Man Arrow Left, Single Sided

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Panel
800-00061	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order