



LCFPRO

CLEVERTRONICS L10 CLEVERFIT PRO EXIT



PRODUCT INFORMATION					
Part Number	LCFPRO				
MIC	UKA01310020001				
Description	L10 Lithium Nanophosphate Cleverfit PRO Emergency Exit, Enabled with Clevertest Plus				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.5kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 				
Luminaire Classification	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px;">X</td> <td style="width: 20px;">1</td> <td style="width: 20px;">AG</td> <td style="width: 20px;">180</td> </tr> </table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598.2.22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LCFPRO
CLEVERTRONICS L10 CLEVERFIT PRO EXIT

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBrkt
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003150	PCA: CT10622-Lx 6C70 CTP UK

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice