



LCFPRO

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms,
Clevertest Plus Enabled, Single or Double Sided



PRODUCT INFORMATION

Part Number	LCFPRO			
MIC	UKA01310020002			
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, All Pictograms, Clevertest Plus Enabled, Single or Double Sided			
Construction	PC/ABS body with PC Diffuser			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	367mm x 72mm x 214mm			
Weight	2.5kg			
Operating Mode	Maintained			
Testing System	Clevertest Plus Enabled (Not activated by default)			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x Duris E3 LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Supply Current	0.049A			
Power Factor	0.39			
Power Consumption	3.4 Watts (Standby), 4.1 Watts (Max)			
Inrush Current (Peak/Duration)	12.8A/82µs			
Earth Leakage	0.339mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Compliance Marking				
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002710	LED Panel
8003858	Emergency Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.