




## LCWELED-D2-DS-R

Classic IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man, Double Sided



### PRODUCT INFORMATION

Part Number	LCWELED-D2-DS-R
MIC	AUA00000023701
Description	Classic IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man, Double Sided
Construction	Polycarbonate white opal cover, glass reinforced nylon PA66 base
Mounting	Ceiling Mount Double-Sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Double Sided, Running Man
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	TBA
Supply Current	TBA
Power Consumption	2.7 Watts (Standby), 5.1 Watts (Max)
Inrush Current (Peak/Duration)	TBA
Earth Leakage	0.358mA
IP Rating	IP66/IP67
Impact Rating	IK10
Operating Temperature	0°C to 40°C
Viewing Distance	24M
AS2293 Classification	C0=D8, C90=D6.3
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002430	Emergency LED Panel
8003062	Node
AUM01270450002	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.