




LCWELED-D2-RL

Classic IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man Left, Single Sided



PRODUCT INFORMATION

Part Number	LCWELED-D2-RL
MIC	AUA00000003901
Description	Classic IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man Left, Single Sided
Construction	Polycarbonate White Opal Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, Ceiling, Single-Sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man Arrow Left, Single Sided
Lamp(s)	6 X LED Lamp Bar Assembly 100,000 Hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby) 5.1 Watts (Max)
Inrush Current (Max)	N/A
Earth Leakage	0.358mA
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
Viewing Distance	24m
AS2293 Classification	C0=D8, C90=D6.3
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002430	LED Strip
AUM01270690001 LCWELEDM-CKIT-D2-83	Driver Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order