



LCWELED-D2-RR

CLEVERTRONICS L10 CLASSIC WEATHERPROOF EXIT DALI-2



PRODUCT INFORMATION

Part Number	LCWELED-D2-RR
MIC	AUA01220640001
Description	L10 Lithium Nanophosphate Classic Weatherproof Exit, DALI-2
Construction	Polycarbonate White Opal Cover, Glass Reinforced Nylon PA66 Base
Mounting	Ceiling Mount, Single-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single Sided, Running Man Arrow Right
Lamp(s)	6 x LED 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.7W (Standby), 5.1W (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D8 C90=D6.3
Impact Rating	IK10
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002430	LED Strip
AUM01270690001	Emergency Driver
LCWELEDM-CKIT-D2-83	
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.