



LCWELED-HVG-DS-RAOW

CLEVERTRONICS CLASSIC WEATHERPROOF EXIT, SURFACE MOUNT,
ZONWORKS XT HIVE 2.4GHz



PRODUCT INFORMATION

Part Number	LCWELED-HVG-DS-RAOW
MIC	AUA01920280001
Description	Classic Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Double Sided, Right Arrow One Way
Construction	Polycarbonate white opal cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby) 5.1 Watts (Max)
IP Rating	IP66/67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D8 C90=D6.3
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002430	LED Strip
AUM01970020001 LCWELEDM-CKIT-HVG-83	Driver Pack
8003560	ZW RF Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.