

## Classic Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided



### PRODUCT INFORMATION

Catalogue Number	LCWELED-HVG-R
MIC	AUA01920030001
Description	Classic Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided
Construction	Polycarbonate white opal cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running man (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.4 Watts (Standby), 4.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D8 C <sub>90</sub> =D6.3
Impact Rating	IK10
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, BRKT.
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
LCWELEDM-CKIT-83	Classic WP Exit, Control Only, 83mA, L10
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.*