



## LFLLED-BLK

Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black



### PRODUCT INFORMATION

Part Number	LFLLED-BLK
MIC	UKT00000003601
Description	Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black
Construction	Polycarbonate
Mounting	Surface Mounted.
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head
Operating Voltage	240V AC; 50Hz
Total Lumen Output	320lm (Emergency total)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Power Factor	0.321
Inrush Current (Max)	14.0A/77us
Earth Leakage	N/A
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598.2.22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
8003143	Driver
1100956	LED Flood Lamp Head
1100957	LED Flood Lamp Head

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice