

LFLLED-HVG-BLK

L10 Optimum Supalite LED Flood Unit, Surface Mounted Emergency Light, Zoneworks Hive, Black



PRODUCT INFORMATION	
Part Number	LFLLED-HVG-BLK
MIC	UKE01810020001
Description	L10 Optimum Supalite LED Flood Unit, Surface Mounted Emergency Light, Zoneworks Hive, Black
Construction	Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head
Operating Voltage	240V AC; 50Hz
Total Lumen Output	320lm (Emergency total)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598.2.22, BS 5266

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





LFLLED-HVG-BLK

LTLLED-HVG-BLK

L10 Optimum Supalite LED Flood Unit, Surface Mounted Emergency
Light, Zoneworks Hive, Black

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
8003143	Driver
1100956	LED Head Assembly, Left
1100957	LED Head Assembly, Right
8003330	Connections Node - HVG

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

