



LFLLED-HVG

Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	LFLLED-HVG
MIC	UKE01810010002
Description	Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive
Construction	Polycarbonate
Mounting	Surface Mounted.
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head
Operating Voltage	240V AC; 50Hz
Total Lumen Output	320lm (Emergency total)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Power Factor	0.321
Inrush Current (Max)	14.0A, 77us
Earth Leakage	N/A
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598.2.22, BS 5266

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533230	Battery
8003851	Driver
1100955	LED Flood Lamp Head
1100954	LED Flood Lamp Head
8003330	Hive Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice