





## LFLLED

Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus



PRODUCT INFORMATION	
Part Number	LFLLED
MIC	UKE01310010002
Description	Supalite Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black
Construction	Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head
Total Lumen Output	320lm (Emergency total)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Power Factor	0.366
Inrush Current (Peak/Duration)	14.0A / 77µs
Earth Leakage	0.319mA
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Compliance Marking	
Luminaire Classification	X   0   AD   180
Conformity	BS EN 60598.2.22, BS 5266
Appliance Class	 Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533230	Battery
8003851	Emergency Driver
1100955	LED Flood Lamp Assembly
1100954	LED Flood Lamp Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order