




## LGELED-80-WM-D2-R

Gigantor 80m Exit, Wall Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man, Single Sided



### PRODUCT INFORMATION

Part Number	LGELED-80-WM-D2-R
MIC	AUA00000002301
Description	Gigantor 80m Exit, Wall Mount, L10 Nanophosphate, DALI-2 Emergency, Running Man, Single Sided
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Compound Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 1 x 6.6V 2500mA (EXIT), 1 x 3.3V 5000mA (EM)
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (Must Specify Diffuser Combination)
Lamp(s)	Exit: LED Strip Module, 4,000K Natural White, Ra>80, LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=39Y/00M), Ta 40°C EM: 2 x 3W LED (Lifetime Warranty on the Lamp head and Loom Assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	16.5W (Standby), 21.8W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Viewing Distance	80m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530190	Battery - Exit
1530230	Battery - Emergency
1100869	Lifelight Pro Head Assembly
8012420	LED Panel - Exit
8012430	
1330054	240V Driver - Exit
AUM01270790001	Emergency Driver - Exit
LCPLED-4W-CKIT- D2	
AUM01270650001	Emergency Driver - Emergency
LLIFE-PRO-CKIT-D2-NP	
8003064	Node - Exit
8003062	Node - Emergency

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.