



LGELED-80-WM-R

Gigantor 80m Exit, Wall Mount, L10 Nanophosphate, Clevertest Plus,
Running Man, Single Sided



PRODUCT INFORMATION

Part Number	LGELED-80-WM-R
MIC	AUA00000001401
Description	Gigantor 80m Exit, Wall Mount, L10 Nanophosphate, Clevertest Plus, Running Man, Single Sided
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Compound Maintained
Testing System	Clevertest Plus
Battery	Lithium Nanophosphate, 1 x 6.6V 2500mA (EXIT), 1 x 3.3V 5000mA (EM)
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (Must Specify Diffuser Combination)
Lamp(s)	Exit: LED Strip Module, 4,000K Natural White, Ra>80, LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=39Y/00M), Ta 40°C EM: 2 x 3W LED (Lifetime Warranty on the Lamp head and Loom Assembly)
Operating Voltage	220-240V~ 50Hz
Supply Current	TBA
Power Factor	TBA
Power Consumption	16.2W (Standby), 21.5W (Max)
Inrush current (Peak/Duration)	TBA
Earth Leakage	TBA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Viewing Distance	80m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530190	Battery - Exit
1530230	Battery - Emergency
1100869	LED Panel - Emergency
8012420, 8012430	LED Panel - Exit
1330054	240V Driver - Exit
AUM01370450001	Emergency Driver - Exit
AUM01370120001	Emergency Driver - Emergency

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.