



LJELED-40-BLK

CLEVERTRONICS L10 JUMBO LED EXIT UNIVERSAL MOUNT, BLACK



PRODUCT INFORMATION	
Part Number	LJELED-40-BLK
MIC	AUA01310010002
Description	L10 Optimum Jumbo Emergency Exit, Enabled with Clevertest Plus, Black
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	630mm x 320mm x 100mm
Cut-Out	N/A
Weight	7.3kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
Inrush Current (Max)	11.6A@82μS
Earth Leakage	0.366mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	40m
AS2293 Classification	C0=D6.3 C90=E3.2
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530031	Battery
AUM01370050001 LJELED-40-CKIT-110	Driver Pack
8002470	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.