



LJELED-40-DALI-BLK

CLEVERTRONICS LP JUMBO LED EXIT UNIVERSAL MOUNT BLACK (DALI)



PRODUCT INFORMATION

Part Number	LJELED-40-DALI-BLK
MIC	AUA01211150002
Description	L10 Optimum LED Wall Mount Jumbo Exit, black, 40 metre Viewing Distance
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface
Dimensions L x W x H	630mm x 320mm x 100mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	220-240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3, C90=E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002470	Emergency LED Strip
AUM01270060102	Emergency Driver Pack
LJELED-40-CKIT-DALI-110	
8003060	Emergency Node – DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.