



LJELED-40-HVG

Jumbo 40m Exit, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LJELED-40-HVG
MIC	AUA01910100001
Description	Jumbo 40m Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Universal Mount
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max, during first 16hr charge)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D6.3 C ₉₀ =E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530031	BATT:L10 3.3V 2.5AH 260mm lead, NB, Slv, Enc
8002470	PCA:Duris E5 Strip for LJELED. CT10050-D2
LJELED-40-CKIT-HVG-110	Jumbo LED Exit, Control Kit, L10, HVG (incl. Hive node)
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.