



LJELED-50-HVG

L10 Optimum Jumbo Emergency Exit, 50 metre viewing Distance,
Zoneworks Hive



PRODUCT INFORMATION

Part Number	LJELED-50-HVG				
MIC	UKA00000034201				
Description	L10 Optimum Jumbo Emergency Exit, 50 metre viewing Distance, Zoneworks Hive				
Construction	Powder coated Metal Frame with Acrylic Diffuser				
Mounting	Surface Mount				
Dimensions L x W x H	630mm x 320mm x 100mm				
Weight	7.3kg				
Operating Mode	Maintained				
Testing System	Zoneworks Hive (RF) 2.4GHz				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	12 x High intensity LED, surface mounted onto a replaceable lamp bar – 100,000hrs				
Operating Voltage	220-240V~50Hz				
Supply Current	0.061A				
Power Factor	0.383				
Total Lumen Output	56lm (Downward Emergency Output)				
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)				
Inrush Current (Peak/Duration)	12.1A / 87µs				
Earth Leakage	0.357mA				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Viewing Distance	50m				
Rated Emergency Duration	180 minutes				
Compliance Marking					
Luminaire Classification	X	1	AFG	180	
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
8002470	LED Panel
UKM00000003601	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice