





## LJWELED-40-HVG

Jumbo 40m IP66 Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Class II



### PRODUCT INFORMATION

Part Number	LJWELED-40-HVG
MIC	AUA01920060002
Description	Jumbo 40m IP66 Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Class II
Construction	Polycarbonate
Mounting	Wall mount, Single-sided Ceiling mount, Single & Double-sided
Dimensions L x W x H	570mm x 117mm x 340mm
Weight	5.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included
Lamp(s)	12 x LED lamp bar assembly 100,000 hours
Operating Voltage	220-240V~50Hz
Power Consumption	3.2W ( Standby)/5.1W ( Max)
IP Rating	IP66
IK Rating	IK09
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D6.3, C90=E4
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	Battery
AUM01970030001	Emergency Driver
8050640	LED Panel
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order