



LJWELED-50-D2

L10 Optimum Jumbo Weatherproof Emergency Exit, 50 Metre Viewing Distance, Universal Mounting, DALI-2



PRODUCT INFORMATION

Part Number	LJWELED-50-D2				
MIC	UKA00000003201				
Description	L10 Optimum Jumbo Weatherproof Emergency Exit, 50 Metre Viewing Distance, Universal Mounting, DALI-2				
Construction	Polycarbonate				
Mounting	Wall Mount, Single-sided Ceiling Mount, Single & Double-sided				
Dimensions L x W x H	570mm x 117mm x 340mm				
Weight	5.6kg				
Operating Mode	Maintained				
Testing System	DALI-2				
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All Directional Inserts Included in the Box				
Lamp(s)	12 x LED Lamp Bar Assembly 100,000 Hours				
Operating Voltage	220-240V~50Hz				
Total lumen output	92lm (Downward Emergency Output)				
Power Factor	0.383				
Supply Current	0.061A				
Power Consumption	3.2W (Standby), 5.1W (Max)				
Inrush Current (Peak/Duration)	11.625A/84µs				
Earth Leakage	0.371mA				
IP Rating	IP66				
IK Rating	IK09				
Rated Emergency Duration	180 minutes				
Viewing Distance	50m				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	1	AFG	180	
Compliance Marking					
Conformity	BS EN 60598-2-22, BS 5266				



LJWELED-50-D2

L10 Optimum Jumbo Weatherproof Emergency Exit, 50 Metre Viewing Distance, Universal Mounting, DALI-2

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533231	Battery
8050640	LED Panel
UKM00000003501	Driver Pack
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.