



# LJWELED-50-DALI

## CLEVERTRONICS L10 JUMBO WEATHERPROOF UNIVERSAL EXIT



### PRODUCT INFORMATION

Part Number	LJWELED-50-DALI				
MIC	UKA01220010002				
Description	L10 Optimum Jumbo Weatherproof Emergency Exit, 50 Metre Viewing Distance, Universal Mounting				
Construction	Polycarbonate				
Mounting	Wall Mount, Single-sided Ceiling Mount, Single & Double-sided				
Dimensions L x W x H	570mm x 117mm x 340mm				
Weight	5.6kg				
Operating Mode	Maintained				
Testing System	DALI Registered				
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All Directional Inserts Included in the Box				
Lamp(s)	12 x LED Lamp Bar Assembly 100,000 Hours				
Operating Voltage	220-240V AC; 50Hz				
Total lumen output	92lm (Downward Emergency Output)				
Power Consumption	3.2W (Standby), 5.1W (Max)				
Viewing Distance	50m				
Rated Emergency Duration	180 minutes				
IP Rating	IP66				
IK Rating	IK09				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery Overvoltage &amp; Overcurrent Protection</li><li>• Battery Deep Discharge Protection</li><li>• Supply Voltage Polarity Reversal Protection</li><li>• Battery Short-circuit Protection (Charging Will Resume Upon Removal of Fault)</li><li>• Kit Box (Enclosure) of Lamp Control Gear Provides Protection Against Accidental Contact with Live Parts</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8050640	LED Panel
UKM01270050002	Driver Pack
8003060	Node - DALI