



LLIFE-2PRO-SMS-600

CLEVERTRONICS L10 LIFELIGHT PRO
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Part Number	LLIFE-2PRO-SMS-600
MIC	AUT01310040003
Description	L10 LifeLight PRO, High Performance, Surface Mount Twin Emergency Light, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface mount and can also be chain suspended
Dimensions L x W x H	611mm x 111mm x 54mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D160 C90=D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt. (QTY 2)
1100869	Lifelight Pro Head Assembly, Gen 2, Round (QTY 2)
AUM01370120001 LLIFE-PRO-CKIT-NP	Lifelight Pro,Control Only,Batten,L10, CTP, OWC,NP (QTY 2)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.