



LLIFE-BLK

Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus, Black



PRODUCT INFORMATION	
Part Number	LLIFE-BLK
MIC	UKD01310060001
Description	Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus, Black
Material	PC/ABS Head
Mounting	Recessed
Dimensions L x W x H	Head Diameter 95mm, 145mm with adapter plate Control Pack 232mm x 51mm x 42mm
Ceiling Hole Cut-Out	85mm, 135mm with adapter plate
Minimum Ceiling Depth	120mm, 70mm with adapter plate
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V, 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 4.2 Watts (Max)
Inrush Current (Peak/Duration)	0.3A / 3668µs
Earth Leakage	N/A
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Total Lumen Output	188lm (Emergency)
IP Rating	IP20
Operating Temperature	0°C to 40°C
Maximum Case Temperature	50°C
Rated Emergency Duration	180 minutes
Compliance Marking	
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533031	Battery
1100922	LED Assembly
UKM01370040003 LLIFE-CKIT-450	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order