



LLIFE-D2-5C

CLEVERTRONICS L10 Lifelight DALI-2



PRODUCT INFORMATION	
Part Number	LLIFE-D2-5C
MIC	AUD01210150001
Description	L10 Lithium Nanophosphate Lifelight, recessed Emergency Light with 5 Core Cable (DALI Cables Brand & Type to be Advised)
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single mint LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W (Standby), 3.0 W (Max)
Inrush	
Earth Leakage	0.000mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	Battery
AUM01270600001 LLIFE-CKIT-D2	Emergency Driver Pack
1100930	Emergency LED Panel
8003062	Emergency Node DALI-2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.