



LLIFE-D2-BLK

Lifelight Emergency, Recessed Mount,
L10 Nanophosphate, DALI-2, Black



PRODUCT INFORMATION

Part Number	LLIFE-D2-BLK	
MIC	UKD01210080001	
Description	Lifelight Emergency, Recessed Mount, L10 Nanophosphate, DALI-2, Black	
Material	PC/ABS Head	
Mounting	Recessed	
Dimensions L x W x H	Head Diameter	95mm, 145mm with adapter plate
	Control Pack	232mm x 51mm x 42mm
Ceiling Hole Cut-Out	85mm, 135mm with adapter plate	
Minimum Ceiling Depth	120mm, 70mm with adapter plate	
Operating Mode	Non-maintained	
Testing System	DALI-2	
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics	
Charging Method	Intelligent current limited constant voltage	
Lamp(s)	1 x LED	
Total lumen output	188lm (Emergency)	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)	
Inrush Current (Max)	0.3A @ 3668µs	
Earth Leakage	N/A	
Rated Emergency Duration	180 minutes	
IP Rating	IP20	
Maximum Case Temperature (TC)	50°C	
Operating Temperature	0°C to 40°C	
Compliance Marking		
Luminaire Classification	X 0 A D F 180	
Conformity	BS EN 60598-2-22, BS 5266	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533031	Battery
1100922	LED Head Assembly
UKM01270120001 LLIFE-CKIT-D2-450	Emergency Driver
8003062	D2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order